

5 BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to an information processing apparatus, an information processing method, and a storage medium for converting print data from a predetermined application program into a data format which can be processed by a printer and outputting the converted data to the printer.

Related Background Art

A print control method and a flow of processes in
15 a conventional print system will now be described with
reference to Fig. 2.

Generally, a print system is constructed by connecting a host computer and a printer through parallel communicating means or network communicating means such as a Centronics interface as shown in Fig. 2.

On the host computer side, application software
201 (hereinafter, abbreviated to "application") such as
word processor or spreadsheet operates on what is
25 called basic software like Windows (registered
trademark of Microsoft Corporation of U.S.A.). In case
of printing in such an application, the printing is

A processing system of the printer driver can be mainly classified into two kinds of a PDL mode type (2023) and an image mode type (2024 to 2026).

The PDL mode type is provided in the case where a controller which processes code data comprising a

5

10

20

25

In both cases, it is necessary to perform the
5 drawing process on the band memory or on the memory
space of a full page by the printer or host machine.

15 According to the data format which is finally
handed to the printer engine, each of concentration
values indicative of a toner color of the printer such
as YMCK values instead of luminance values of RGB
consists of one or two bits per color. Therefore,
20 generally, the process is performed by one or two bits
per color of YMCK in both the image mode and the PDL
mode in order to reduce the memory capacity. In the
image mode, by sending the 1-bit or 2-bit data per
color of YMCK, a transmission data size is reduced,
25 thereby decreasing a load on the printer side.

For example, with respect to a printing process of a polygonal figure, in the PDL type, point coordinates

mode, the drawing process is performed on the device dependent color space in a manner like one or two bits per color of YMCK in order to save the memory capacity. However, since a logical operation drawing process
5 specified by the GDI is a process on a luminance space, an improper drawing sometimes occurs. To avoid it, the YMCK values are returned to the RGB values and a (inverse UCR (Under Color Remove) process) logical calculating process is performed. However, not only
10 the perfect drawing process is not guaranteed but also it becomes a cause of reduction of the processing speed.

Therefore, the user ordinarily performs the drawing process in the PDL mode and if it takes time to
15 output, the operating mode is switched to the high speed image mode (image mode of one bit per color of YMCK) and the data is outputted again. If an improper output result is obtained, the data is outputted again in an RGB 24 BPP image mode. In this manner, the user
20 has to perform the operation two or more times.

That is, the user has to select the print mode in the present situation and the optimum mode cannot be known unless the data is printed in all of the modes. If pages of different types are included in a multipage
25 printing mode, a problem such that it takes a long output time in one mode or an improper output page is mixed occurs.

00000000-00000000

5

0

15

20

25

(4) In the print data format (image mode processing) having a low abstraction degree, even in case of a page comprising only simple characters or figures, the image data that is proportional to a draw area is transmitted

to the printer. Therefore, the maximum throughput of an engine cannot be derived.

(5) In the multipage printing mode, it is difficult to print to all pages in the optimum mode.

5

SUMMARY OF THE INVENTION

The items (1) to (4) among the above subjects are the features of the processing systems and cannot be said to be drawbacks. The present invention intends to improve the whole system by supplementing the disadvantages of the other processing systems with the advantages of the processing systems.

That is, it is an object of the invention to select optimum converting means in accordance with the print data and print at a high speed.

Another object of the invention is to perform an N-up printing at a high speed.

To accomplish the above objects, according to a preferred aspect of the invention, there is provided an information processing apparatus comprising:

first converting means for converting print data into image data;

second converting means for converting the print data into code data for allowing a printer to generate the image data;

predicting means for predicting a printing time using the image data converted by the first converting

004290" 80050960

means and a printing time using the code data converted by the second converting means;

discriminating means for discriminating whether the printing time using the image data is shorter than the printing time using the code data or not on the basis of a prediction result by the predicting means; and

selecting means for selecting the first converting means when it is determined by the discriminating means that the printing time using the image data is shorter and selecting the second converting means when it is determined by the discriminating means that the printing time using the image data is not shorter.

According to another aspect of the invention, there is provided an information processing apparatus comprising:

first converting means for converting print data into image data;

second converting means for converting the print data into code data for allowing a printer to generate the image data; and

selecting means for selecting either the first converting means or the second converting means on a logical page unit basis.

According to still another aspect of the invention, there is provided an information processing apparatus comprising:

004290" 80050960

transmitting means for selecting a renderer in accordance with the mode set by the setting picture plane, converting print data by using the selected renderer, and transmitting the converted print data to a printer.

Fig. 1 is a side sectional view showing a structure of a laser beam color printer to which an embodiment of the invention can be applied;

Figs. 3A and 3B are block diagrams showing a basic construction of a whole print system according to the embodiment of the invention;

Fig. 5 is a diagram showing a flowchart showing a flow of a checking method of each object upon spooling of the invention;

Fig. 7 is a schematic diagram showing a method of

forming a band list upon despooling of the invention;

Fig. 8 which is composed of Figs. 8A and 8B are diagrams showing a flowchart showing a flow of a process for forming a band list upon despooling of the invention;

5 Fig. 9 is a diagram showing a structure of a PDF;

Fig. 10 is a diagram showing a structure of a PCF;

Fig. 11 is a schematic diagram for explaining a virtual band for holding a result checked at the time of the spooling;

10 Fig. 12 is a schematic diagram showing features of processing times of an image mode processing and a PDL mode processing;

Fig. 13 is a flowchart showing a flow of a process for determining a processing mode when it is seen on a physical page unit basis according to the invention;

15 Fig. 14 is a flowchart showing a flow of a process for determining a processing mode when it is seen on a logical page unit basis according to the invention;

20 Fig. 15 is a schematic diagram showing the structure of the PCF;

Fig. 16 is a schematic diagram of an ideal embodiment of the invention;

Fig. 17 is a diagram showing a despooling process at the time of an N-up process;

25 Fig. 18 is a diagram for explaining a print command generating process at the time of the N-up process;

00605008-062700

Fig. 19 is a diagram showing a graphic mode selecting picture plane; and

Fig. 20 is a diagram showing a graphic mode selecting process.

5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Prior to explaining a construction of the embodiment, a structure of a color laser beam printer (hereinafter, referred to as a "color LBP") for performing the printing of a print system to which the embodiment is applied will be first described with reference to Fig. 1.

Fig. 1 is a side sectional view showing the structure of a color LBP for recording an image on the basis of multivalue data which has a resolution of 600 dots per inch (dpi) and in which each pixel of each color component is expressed by 8 bits. In Fig. 1, reference numeral 100 denotes a color LBP main body serving as an apparatus for inputting and storing print data comprising print data (character codes, image data, etc.) and control codes which are supplied from a host computer or the like connected to the outside of the LBP, generating corresponding character patterns, images, or the like in accordance with those information, and forming an image onto a recording paper as a storage medium.

Reference numeral 110 denotes a format controller

004290" 80050960

for analyzing the print data which is supplied from the
host computer, generating a print image, and
controlling the color LBP main body 100. The format
controller 110 is connected to an operation panel 120
5 on which switches, an LED display, and the like for
allowing the user to operate and notifying the user of
a status of the LBP have been arranged. The operation
panel is arranged as a part of an outer casing of the
printer 100. The final print image generated by the
10 format controller 110 is transmitted as a video signal
to an output controller 130. The output controller 130
receives status information from various sensors (not
shown) of the printer 100, outputs control signals to
an optical unit 140 and various driving system
15 mechanism portions, thereby controlling a printing
process as a printer 100.

In the printer shown in Fig. 1, a front edge of a
paper P fed from a paper feed cassette 161 is gripped
by a gripper 154f and the paper is held around an outer
20 periphery of a transfer drum 154. A latent image of
each color formed on a photosensitive drum 151 by the
optical unit 140 is developed by each of color
developing devices Dy, Dm, Dc, and Db of yellow (Y),
magenta (M), cyan (C), and black (B) and transferred
25 onto the paper wrapped around the transfer drum a
plurality of number of times, so that a multicolor
image is formed. After that, the paper P is separated

from the transfer drum 154, fixed by a fixing unit 155,
and ejected from a paper discharging portion 159 to a
paper discharge tray 160. Each of the developing
devices Dy, Dm, Dc, and Db of the respective colors has
5 rotary spindles at both ends and is held to a developer
selecting mechanism 152 so as to be rotatable around
the spindle as a rotational center. Thus, each of the
developing devices Dy, Dc, Db, and Dm has such a
construction that even if the developer selecting
10 mechanism 152 rotates around a rotary shaft 152a as a
center in order to select the developing device as
shown in Fig. 1, its position can be maintained to be
constant. After the selected developing device was
moved to a developing position, a selecting mechanism
15 holding frame 153 is pulled toward the photosensitive
drum 151 by a solenoid 153a around a fulcrum 153b as a
center, so that the developer selecting mechanism 152
is moved toward the photosensitive drum 151 together
with the developing devices, thereby performing a
20 developing process. Subsequently, the photosensitive
drum 151 is uniformly charged to a predetermined
polarity by a charging device 156. Print information
developed as an image in the format controller 110 is
converted into a video signal of a corresponding
25 pattern and is outputted to a laser driver and drives a
semiconductor laser 141. A laser beam which is emitted
from the semiconductor laser 141 is on/off controlled

004290" 8050960

in accordance with the inputted video signal and is further swung right and left by a polygon mirror 142 which is rotated at a high speed by a scanner motor 143 and scans and exposes on the photosensitive drum 151 through a polygon lens 134 and a reflecting mirror 144. Thus, an electrostatic latent image of the image pattern is formed on the photosensitive drum 151. Subsequently, for example, the electrostatic latent image of M (magenta) color is developed by the developing device Dm of M (magenta) color and a first toner image of M (magenta) color is formed on the photosensitive drum 151. On the other hand, the transfer paper P is fed at a predetermined timing, a transfer bias voltage of an opposite polarity (for example, plus polarity) of that of the toner is applied to the transfer drum 154, the first toner image on the photosensitive drum 151 is transferred onto the transfer paper P, and the transfer paper P is electrostatically adsorbed to the surface of the transfer drum 154. After that, the toner of M (magenta) color remaining on the photosensitive drum 151 is removed by a cleaner 157, thereby preparing for a step of forming and developing a latent image of the next color. The toner images of the second, third, and fourth colors are sequentially transferred in the order of C (cyan), Y (yellow), and Bk (black) by a similar procedure. However, the transfer in this case differs

09605008-062700
001290" 80050960

5 When a front edge portion of the transfer paper P on
which the toner images of four colors have been
multiplexed and transferred approaches a separating
position, a separating claw 158 approaches and its
front edge is come into contact with the surface of the
10 transfer drum 154, thereby separating the transfer
paper P from the transfer drum 154. The separated
transfer paper P is conveyed to the fixing unit 155.
The toner image on the transfer paper is fixed by the
fixing unit and the resultant paper is ejected onto the
15 paper discharge tray 160. The color laser beam printer
in the embodiment outputs an image at the resolution of
600 dots per inch (dpi) by the image forming step as
mentioned above. The printer to which the invention
can be applied is not limited to the color LBP but can
20 be applied to another color printer of another print
system such as ink jet printer, thermal printer, or the
like.

25 Usually, the format controller is a portion which is
 also called a PDL controller or the like and comprises:
 an interface (I/F) 111 as connecting means with the host

computer; a reception buffer 1121 for temporarily holding and managing the reception data or the like; a transmission buffer 1122 for temporarily holding and managing the transmission data or the like; a command analyzer 113 for analyzing the print data; a print controller 114; a drawer 115; a page memory 116; and the like.

The interface (I/F) 111 is communicating means for transmitting and receiving the print data to/from a host computer 200 and enables communication which conforms with IEEE-1284 as a communication protocol. The invention, however, is not limited to such communicating means but can be applied to a connection by various protocols through a network or to communicating means which conforms with IEEE-1394. The print data received through the I/F 111 is successively accumulated in the reception buffer 1121 as memory means for temporarily holding the data and is read out and processed as necessary by the command analyzer 113 or drawer 115. The command analyzer 113 is constructed by a control program according to each PDL command system or a print job control language. As for an analysis result of the print data regarding the drawing of character printing, figure, image, or the like, the command analyzer gives an instruction to the drawer 115 and processes such an analysis result. As for a command such as paper feed selection command, reset

09605008-062700

The drawer 115 is a renderer for successively developing each drawing object such as characters or image into the page memory 116. Although it is necessary to area-sequentially (of MCYK) transmit device dependent bitmap data to the color LBP mentioned in Fig. 1, the whole memory necessary for such a purpose is not always assured in the normal state but a memory is assured as a band area of a fraction of an integer of one plane (1, 2, or 4 bits/pixel), the band area is efficiently used, and the image is processed synchronously with the engine speed. Usually, the page memory 116 is managed by the chase of the developing process by the YMCK renderer and the shipping of the video signal to a printer engine as mentioned above, namely, by a banding control. However, if there is a sufficient memory capacity, an area in which the data of one page can be developed can be also assured. Generally, the format controller 110 is constructed by a computer system using a central processing unit (CPU), a read only memory (ROM), a random access memory (RAM), and the like. The processes in each section can be executed on a multitask monitor (real-time OS) in a time-sharing manner or can be also independently executed by preparing dedicated controller hardware

every function.

The operation panel 120 is used to set and display various statuses of the printer as mentioned above.

The output controller 130 converts the contents in the

5 page memory 116 into the video signal and transmits an image to a printer engine ¹⁴⁰150. The printer engine ¹⁴⁰150

is a print mechanism for permanently forming a visible image onto the recording paper on the basis of the

received video signal and has already been mentioned in

10 Fig. 1. The printer 100 has been described above. A

whole construction of the print system in the

embodiment including a host computer 300 will now be

described. In Figs. 3A and 3B, reference numeral 300

denotes a host computer for outputting the print

15 information comprising the print data and control codes

to the printer 100. The host computer 300 is constructed

as one computer system comprising: a keyboard 310 as an

input device; a mouse 311 as a pointing device; and a

display monitor (hereinafter, simply referred to as a

20 monitor) 320 as a display device. It is assumed that

the host computer 300 operates on the basis of the

basic OS such as Windows NT or the like.

On the host computer side, when the functions on the basic OS are largely classified by paying attention

25 only to the functional portions regarding the

invention, they are mainly classified into: application

software 301; a graphic subsystem 302; and a spool

002290" 80050960

subsystem 303 including communicating means with print information storing means and the printer.

5 The application software 301 indicates, for example, application software such as word processor, spreadsheet, or the like which operates on the basic software. The graphic subsystem 302 comprises: a Graphic Device Interface(hereinafter, referred to as a GDI) 3021 as a part of the functions of the basic OS; and a printer driver 3022 as a device driver which is
10 dynamically linked from the GDI.

The printer driver 3022 is called from the GDI through an interface called DDI (Device Driver Interface) and executes a process according to the device every drawing object. In the system,
15 information handed to a DDI function is spooled as PDF (Page Data File) 3031 on a page unit basis. However, in this instance, by calling a PreCheck module 3023 as a module for checking the drawing information from the printer driver 3022, the data included in the page is
20 analyzed. By analyzing the data of one page, the draw commands included in the page are classified every kind and sum-up results of the number of calling times and the data size are formed. The drawing area in the page is obtained as an outermost circumscribed rectangle.

25 The above results are named by a name associated with the corresponding PDF 3031 through the GDI and saved as a PCF 3032 (the substance is saved on the RAM or

004290" 80050960

5

5

5

15

25

processing (3034 to 3037), the selected translator
(3035 to 3037) develops the image by using a band
memory 3038 and generates a PDL command of a device
dependent bitmap format. In case of a PDL mode
5 processing (3034), the selected translator converts the
spool file into the PDL command. The generated PDL
command allows the data to be transmitted to the
printer via a GDI (3039) and an I/F (3040).

002290" 80050960
10 Although there is a case where the foregoing names
and functional combinations slightly differ in
dependence on the basic OS, so long as a module which
can realize each technical means in the invention, the
names and functional combinations are not a large
problem in the invention. For example, what is called
15 a spooler or spool file can be also realized by
assembling the processes into a module called a print
queue in another OS. Generally, in the host computer
300 including those functional modules, under the
hardware such as central processing unit (CPU), read
20 only memory (ROM), random access memory (RAM), hard
disk drive (HDD), various input/output controllers
(I/O), and the like, the software called basic software
performs their controls, and under this basic software,
each application software and a subsystem process
25 operate as functional modules.
(Further detailed description of the printer driver on
the host side)

To realize the invention, at least the following functions are necessary in the printer driver which operates in the host machine.

- 1) draw data spool process
- 5 2) check and driver switching process
- 3) various drivers

The above functions will be described hereinbelow.

- 1) Draw data spool process

Explanation will be made with respect to Windows
10 NT4.0 with reference to Fig. 9.

In Windows NT4.0, the following functions can be mentioned as drawing DDI functions which are called from the GDI.

DrvCopyBits(), DrvBitBlt(), DrvStretchBlt(),
15 DrvStrokePath(), DrvFillPath()
DrvStrokeAndFillPath(), DrvPaint(), DrvTextOut()

The drawing objects are handed to those functions from the GDI through arguments.

For example, the arguments of DrvCopyBits() as a
20 drawing processing function of an image are as follows.

```
BOOL  DrvCopyBits(  
    SURFOBJ  *psoDest,  //handle linked to memory of  
                        the drawing destination  
    SURFOBJ  *psoSrc,   //handle linked to source  
25           data  
    CLIPOBJ  *pco,      //handle of clip information  
    XLATEOBJ *pxlo,     //handle of color conversion
```

004290" 80050960

```
RECTL      *prclDest, //rectangular area of drawing
              destination
POINTL     *pptlSrc    //upper left coordinates of
              source data
```

)

In the PDL mode, the clip data is first obtained from pco, clipping designation data is issued, and after that, the image draw data is generated and issued so that the source image data on the destination side shown by psoSrc and pptlSrc is drawn to the destination shown by psoDest and prclDest. In the image mode, it is sufficient to copy the image shown by psoSrc and pptlSrc to the destination shown by psoDest and prclDest only into the area shown by pco.

To realize the invention, it is necessary to determine the optimum processing mode and execute the process in this mode after the draw data of one page was detected. For this purpose, the data handed to the DDI function is once spooled and the optimum mode is decided in this instance. After it was decided, the spooled data is executed in the decided mode, so that the above process can be realized.

For this purpose, in the data which is handed to the DDI function, it is necessary to spool the data which can be processed even if the mode is determined to be any mode upon despooling.

First, it is necessary to hold the spool data on a page unit basis. Therefore, a PDF 900 holds page information (902), as a header, holding the page size, data size, the number of stored objects, and the like subsequently to pageID (901) to specify the page.

After the header, a number 903 showing the drawing function called by the DDI function is arranged. DrvCopyBits will be explained here as an example.

datasize (904): Size related to spooling of DrvCopyBits.

soDset (905): The data which can be obtained by psoDest showing surface data of the drawing destination which is handed to the DrvCopyBits() function is stored.

SoSrc (906): The data which can be obtained by psoDest showing source surface data which is handed to the DrvCopyBits() function is stored.

Source image data (907): The substance of source image data which can be obtained from psoSrc.

co (908): The data which can be obtained from pco showing clip data of the drawing destination which is handed to the DrvCopyBits() function is stored. If the clip data exists, clip data (909) is stored after that.

xlo (910): The data which can be obtained by pxol showing color conversion data which is handed to the DrvCopyBits() function is stored.

002290"80050950

rclDest (911): The data which can be obtained from
prclDest showing a rectangle on the surface of the
drawing destination which is handed to the DrvCopyBits(
) function is stored.

5 ptlSrc (912): The data which can be obtained from
pptlSrc showing from which position on the source
surface which is handed to the DrvCopyBits() function
the drawing is performed is stored.

10 After that, spools of the data that is necessary
for each drawing function continue for one page.

15 Upon despooling, the despooler returns the data to
the spooled information and hands it to the DDI
function of the selected driver, so that the printer
driver so far can operate in the DDI function
specifications as they are.

2) Check and driver switching process

20 The check and driver switching means analyzes the
data of the spool data by checking the following points
when the draw data which is handed to the printer
driver is spooled. In the embodiment, when the draw
data of (1) is spooled, the data regarding the mode
switching is obtained and set into a data structure
like a PCF (precheck file) in Fig. 10, thereby
realizing.

25 <1> color data check

Even in case of the color printer, the check and
driver switching means sets a monochromatic mode into a

00605008-062700
002290"80050960

default status, thereby allowing the printer to operate in the color mode when at least one color data exists in the draw data. In a PCF 1000, although the set color mode is registered in 1003, a value indicative of the monochromatic mode at the time of initialization is set into desiColMode (1004) and colflg (10098) of each band information. When the draw data is spooled, if there is an object which designates a chromatic color, desiColMode (1004) and colflg (10098) of the corresponding band are reset to the color mode.

After the end of the check of the whole page, if desiColMode (1004) of the page indicates the monochromatic mode, by handling the page as a monochromatic mode, the number of rotating times of the drum is suppressed to one. Even when desiColMode (1004) of the page indicates the color mode, if colflg (10098) has been determined to be the output in the monochromatic mode and the Device image mode, by performing the drawing process to the band in the K1 (2, 4) BPP image mode, the drawing process of a large band area at the same band memory size can be performed.

In the color LBP printer, the photosensitive drum rotates 4 times, so that the toner of the colors of YMCK is transferred to the drum surface in the color printing mode. However, in the monochromatic mode, it rotates only once to transfer only the black toner to

002290"80050960



Therefore, according to the embodiment, such a drawback is avoided by predicting the data size in the printer in the PDL mode.

15

25

To obtain the data size in the case where the data is sent in the image mode, the maximum rectangular size of the drawing area of the draw data is updated to

BandRendRectL of each band information. When
PDLDataSize (10096) is larger than that in the case
where BandRectL (10094) of the whole band area has been
sent by the image data with respect to each band, it is
5 determined to process such a band in the Device image
mode (1, 2, or 4 bits per color of YMCK) and a decision
result is recorded in desiMode (10092).

<3> Drawing speed check

In a printer in which the memory saving is
10 realized by the banding process in the PDL mode, if
there are many drawing objects in the same band, the
drawing time is later than the shipping time and the
drawing by the banding process becomes impossible. In
the normal printer, in such a case, the data is
15 outputted by entering a special path for getting the
memory size of one page. However, if there is not a
sufficient memory capacity in the printer, the
compressing and decompressing processes of the image
data drawn on the band memory are often executed, so
20 that the processing speed decreases.

In the embodiment, therefore, the drawing time per
unit area is predicted and, as for the area in which
the drawing time is later than the shipping time, it is
determined to develop the data into the data in the
25 Device image mode (1, 2, or 4 bits per color of YMCK)
and send the data to such an area, or the processes of
the printer can be reduced by a method of sending the

002290-00050960

data of the whole page in the Device image mode.

In the embodiment, the data type and the drawing process prediction time in the printer at the time when the data is sent in the PDL mode are predicted in a manner similar to the case <2> and accumulated into rendTime (10093) every band corresponding to the drawing area.

As for the band in which the value of the predicted drawing time is longer than the shipping time, desiMode is set into the Device image mode (1, 2, or 4 bits per color of YMCK).

<4> Logical operation value check

It is an object to equalize the drawing process in the printer with the output result on the display. For this purpose, there are many systems such that the logical operating process in an RGB space (luminance color space) used for the display or an operating process using an α channel are designated for the printer driver as they are. However, since the printer print the image by using the toner or ink, the band memory or page memory is assured by one or two bits per color of YMCK as concentration color space values and used as a drawing plane. There is, consequently, a case where the print result does not become an expected logical operation result. To avoid it, it is necessary to set the RGB24BPP image mode for performing the drawing process on the memory using a memory space of 8

00000000-00000000

In the embodiment, the improper drawing is avoided by switching so as to process in the RGB24BPP image mode in such a case.

The optimum mode can be selected by performing the checking process mentioned above every drawing object. Although the unit for the mode switching can be set to the maximum job unit or the minimum object unit, if effect of raising the speed by the mode switching is expected, at least the switching process of the page unit is necessary.

The band unit used here does not indicate the band which is used for the drawing process by the printer or

It is desirable that the band height size is equal to or lower than the minimum band height in the drawing process which is executed in the printer driver.

Fig. 5 shows a flow of processes which are executed when the draw data is handed to the printer driver and this processing routine is executed each time the draw data is called. A program regarding the flowchart of Fig. 5 is stored in the memory of the host computer 300 and executed by the CPU.

S502: Whether all of the bands in the range where the present object is drawn have been determined to be the RGB24BPP image mode or not is discriminated. If YES, step S509 follows. If there is another mode, step S503 follows.

S503: Whether the drawing logic of the present object is possible on the device color space or not is discriminated. If YES, step S504 follows. If NO, step

one page will now be described with reference to a flowchart of Fig. 6. A program regarding the flowchart of Fig. 6 is stored in the memory of the host computer 300 and executed by the CPU.

5 S601: Whether a color object flag of the checking
band in 700 in Fig. 7 has been set to "1" or not is
discriminated. If YES, step S602 follows. If NO, step
S603 follows.

S602: The present page is set to the color mode.

10 Step S603 follows.

S603: Whether the present band has been set to the PDL mode or not is discriminated. If YES, step S604 follows. If NO, step S607 follows.

S604: The data size in the printer in the case where
15 the data has been sent in the image mode is compared
with that in the case where the data has been sent in
the PDL mode. If the data size in the case where the
data is sent in the PDL mode is larger, step S606
follows. If the data size in the case where the data
20 is sent in the image mode is larger, step S607 follows.

S606: The present band is set to the Device image mode. In step S606, the image mode is set to one of the YMCK 1-bit mode, 2-bit mode, and 4-bit mode on the basis of the setting of the user. Step S607 follows.

25 S607: Whether the processes of all bands of the
present page have been completed or not is
discriminated. If YES, step S608 follows. If NO, step

S601 follows.

S608: The modes determined with respect to all bands of the present page are linked to the page ID and spooled as a precheck file (PCF).

- 5 3) Finally, the drawing process which is executed by various drivers in accordance with the determined mode will be explained with reference to Fig. 7.

10 It is assumed that by checking the page of 700 in the item (2), a decision is made as shown in 710. Band delimiters of 700 and 710 are virtual bands for checking.

15 Reference numeral 701 denotes image data of a high resolution. If it is converted into a PDL command in a state of a value of 8 bits per color of RGB, a data capacity becomes tens of Mbytes. Therefore, the second and third bands are determined to draw in the YMCK4BPP (one bit per color) image mode.

20 Reference numeral 702 denotes draw data in which an improper drawing occurs when the YMCK drawing process is performed. Therefore, the corresponding band is determined to perform the drawing process in the RGB24BPP image mode. Reference numeral 710 denotes that it is determined that there is no problem in the PDL mode with respect to the other bands.

25 A despooler 3033 forms band information for despooling on the basis of the virtual band data handed as mentioned above.

002290" 80050960

5

10

15

20

25

vH = Height of virtual band (band height shown at

710 in Fig. 7)

maxH = Maximum height which can be obtained in the case where the band memory which could be obtained is used by each renderer (upper portion of 7201 in Fig. 7 and band height shown at 7203)

```
nowBH = Processing band height which is being
        calculated at present
```

S801: The PCF (file in which the result checked upon spooling has been stored) corresponding to the page to be outputted is opened. Step S802 follows.

S802: The drawing mode necessary for the drawing process of the present page is detected. An initializing process of nowBH to store the band height which is being calculated at present is also performed. Step S803 follows.

S803: In case of only the PDL mode, step S813 follows. When there is the image mode, step S804 follows.

S804: The band memory which can be used as an image mode is obtained. The maximum value maxH of the band height for drawing process is obtained from the obtained band memory size, page lateral width size, and the value of bits/pixel of each mode. Step S805 follows.

S805: The next virtual band information is obtained.
Step S806 follows.

S806: Whether the processing mode is the same as

S807: If any value other than 0 exists in nowBH, the band of the height in nowBH is registered together with the drawing position and the drawing mode and initialized to nowBH = 0. If 0 exists in nowBH, this step is skipped and step S808 follows.

S809: The virtual band space is divided into $(vH + \text{nowBH})/\text{maxH}$ (integer obtained by omitting the fraction below decimal point: for example, portion of 2 of 256/100 = 2.56) bands of the maxH height and registered together with the drawing mode. $\text{nowBH} = (vH + \text{nowBH})\% \text{maxH}$ (remainder portion of the division: for example, portion of 56 of 256/100 = 2 and remainder 56) is set. Step S811 follows.

S811: When the reading process of all of the virtual bands is finished, step S812 follows. If NO, step S805 follows.

S812: If any value other than 0 exists in nowBH, the
25 band of the height in nowBH is registered together with
the drawing position and the drawing mode and
initialized to nowBH = 0. If 0 exists in nowBH, the

processing routine is skipped and step S813 follows.

S813: A band list is formed on the basis of the band data registered in steps S807 and S809 and the spooled draw data is linked to the band list. Step S814 follows.

S814: The drawing process or the converting process for converting the data into the PDL data is executed from the upper bands registered in the band list and the generated data is transmitted to the printer.

S815: The spooled draw data is read, converted into the PDL commands in the registering order, and transmitted to the printer.

In step S814, if the YMCK mode has been set in step S507 and the image mode of 1BPP per color of YMCK has been designated by the user, the RGB24BPP image is converted into the YMCK1BPP image by a YMCK renderer 3036 and the operation, the drawing process are performed on the basis of the YMCK1BPP image, and the resultant data is outputted to the printer.

In the case where the YMCK mode has been set and the 2BPP image mode per color of YMCK has been set by the user in step S507, the RGB24BPP image is converted into the YMCK2BPP image by the YMCK renderer 3036 and the arithmetic operation and the drawing process are performed by the converted YMCK2BPP image, and the YMCK2BPP image is outputted to the printer. In the case where the YMCK mode has been set and the YMCK4BPP

002290"80050960

5 YMCK4BPP image, and the YMCK4BPP image is outputted to
the printer. In the case where the RGB mode has been
set in step S508, the arithmetic operation and the
drawing process are performed in the RGB24BPP image
mode by the RGB renderer 3037, the image is converted
10 into the 1, 2, or 4 BPP image per color of YMCK
designated by the user and the converted image is
outputted to the printer.

(Further detailed description on the printer side)

20 <1> Processing mode switching function of the band
 unit or page unit.

25 However, in the image mode, since the data is processed
by a special memory construction in order to process a
large amount of image data at a high speed, it is

To realize the invention, it is necessary to switch the PDL mode and the image mode on a page unit basis and, further, on a band unit basis.

It will be obviously understood that in order to switch the mode for performing the drawing process on a band unit basis, in the case where there are the objects to be drawn over the band, drawing algorithms also have to be matched lest a discontinuous line appears.

The second embodiment of the invention will now be described with reference to Fig. 16.

Reference numeral 1601 denotes a document of four pages formed by using a general document forming application. The first to third pages are constructed by data of only characters and are pages which can be

printed at a high speed by the printer. However, image data 1602 adhered to the fourth page is a color image of a high resolution. If a multipage (4-up) on which four pages are printed to one page is processed in the PDL mode, the high resolution image is transmitted to the printer as a PDL command as it is and the processing speed of the printer remarkably deteriorates.

To avoid it, the processing system is automatically switched by using the invention. In the N-up printing mode, the following two switching methods can be mentioned.

1) They are switched on a physical page unit basis.

To process the whole physical page including the high resolution image in the image mode, the whole page is divided into several band areas (1603), the drawing process is executed on a band unit basis, and the generated device bitmap data has a size of the whole page. (in the case where the resolution is set to 600 dpi, the number of output gradations is equal to 2, the printing mode is the YMCK printing mode, and the size is set to the A4 size, the data size at the time of non-compression is equal to 32 Mbytes. Therefore, a possibility in which the data cannot be outputted by the designated number of gradations is high in dependence on the size of memory installed in the printer.)

2) They are switched on a logical page unit basis.

As for the first to third pages, only a character draw command using character codes is generated by a translator of the PDL mode system. As for the fourth
5 page, a translator of the image mode system is selected. According to the translator of the image mode system, a band memory of the area at the time when a reducing process was performed is prepared (1605). To draw the reduced image into such a band memory, the
10 number of times of band division and the generated device bitmap data are also reduced into 1/4 of that in the case of 1). Even when the size of the installed memory is small in correspondence to it, a possibility in which the data is outputted at a high gradation by
15 the image mode processing is high.

The invention uses the method of 2). A method of realizing such a method will now be described in detail hereinbelow.

(Further detailed description of the printer driver on
20 the host side)

To realize the invention, at least the following functions are necessary for the printer driver which operates by the host machine.

1) Draw data spooling process

25 2) Checking process and drawing area holding process of each draw command upon spooling

3) Process for reading device information, output

002290"80050360

environment information, layout information, and check results before despooling

4) Process for selecting reproducing means and the number of output gradations from the check results on a logical page unit basis

5) Process for performing the despooling process by the processing system selected by the selected reproducing means every logical page and ejecting the page on a physical page unit basis

Each of the above processes will be described hereinbelow.

1) Draw data spooling process

This process will be explained with reference to Fig. 9 with respect to Windows NT4.0 as an example.

In Windows NT4.0, the following functions can be mentioned as DDI functions for drawing which are called from the GDI.

DrvCopyBits(), DrvBitBlt(), DrvStretchBlt(),
DrvStrokePath(), DrvFillPath()

DrvStrokeAndFillPath(), DrvPaint(), DrvTextOut()

The drawing objects are handed to those functions from the GDI through the arguments.

For example, the arguments of DrvCopyBits() as a drawing processing function of an image are as follows.

BOOL DrvCopyBits(
SURFOBJ *psoDest, //handle linked to memory of
the drawing destination

00000000 00000000 00000000 00000000

page unit basis. Therefore, the PDF 900 in Fig. 9 has the page information (902) to hold the page size, data size, the number of stored objects, and the like as a header subsequently to the pageID (901) for specifying the page.

After the header, the number 903 indicative of the drawing function called by the DDI function is arranged. Explanation will now be made with respect to DrvCopyBits as an example.

datasize (904): Size related to spooling of DrvCopyBits.

soDset (905): The information which can be obtained by psoDest showing surface information of the drawing destination which is handed to the DrvCopyBits() function is stored.

soSrc (906): The information which can be obtained by psoDest showing source surface information which is handed to the DrvCopyBits() function is stored.

source image data (907): The substance of source image data which can be obtained from psoSrc.

co (908): The information which can be obtained from pco showing clip information of the drawing destination which is handed to the DrvCopyBits() function is stored. If the clip data exists, clip data (909) is stored after that.

xlo (910): The information which can be obtained by pxol showing color conversion information which is

002290"80050960

5

10

15

20

25

The checking means and the drawing area holding means of each draw command upon spooling analyze the information of the spool data by checking the following points regarding the processing speed when the draw data which is handed to the printer driver is spooled. In the embodiment, when the draw command of (1) is spooled, the information regarding the mode switching is obtained, stored, and spooled into a data structure like a PCF (precheck file) 1000 in Fig. 15 on a page

unit basis, thereby realizing.

The data structure of the PCF 1000 is a structure starting from a job number 1001 and a page number 1002 to which such a file belongs, and the corresponding
5 page can be specified by those two values.

The other structure is constructed by a bandinf structure 1030 in which each of the bands obtained by dividing the page in the Y axis direction is used as a unit. As for a virtual area, the band area in which
10 the bands of the size shown in VbandSize 1004 of the number corresponding to bandCnt 1005 are filled in the pageSize 1003 is virtually defined.

BandInfo is a structure starting from BandRectL 1010 which holds the area of the virtual band by
15 rectangle information. This structure is a structure to record the concerned drawing processing information into the area of BandRectL 1010. The details are as follows.

- A maximum circumscribed rectangular area DrawRectL
20 1011 of the drawing process which is drawn in the band.
- A chromatic color area ColorRectL 1012 in the drawing area which is drawn in the band.
- An area ROPRectL 1013 in which an improper printing occurs when the YMCK printing is performed.
- 25 • A drawing processing area ImgRectL 1014 by the image system function.
- A drawing area GraphicRectL 1015 by the graphic

002290" 80050950

function.

- A character system drawing area TextRectL 1016.

The areas shown by the above RectL structures are shown in Fig. 11 so as to be easily understood.

5 1101: Outermost rectangular area of the drawing area in each virtual band held in DrawRectL 1011.

1102: Outermost rectangular area of the drawing area where the drawing process is performed by the chromatic color in each virtual band held in ColorRectL 1012.

10 1103: Outermost rectangular area of the drawing area in each virtual band held in ROPRectL 1013.

1104: Outermost rectangular area of the drawing area of the image system in each virtual band held in ImgRectL 1014.

15 1105: Outermost rectangular area of the drawing area of the graphic system in each virtual band held in GraphicRectL 1015.

20 1106: Outermost rectangular area of the drawing area of the character system in each virtual band held in CharRectL 1016.

25 The outermost rectangular area of the drawing area presumed from the draw command is obtained when the draw data is spooled and the above area shows an overlap portion of the outermost rectangular area and bandRectL.

Besides them, the BandInfo structure 1030 collects the information of each DDI function into areas 1017 to

002290-80050360

1020.

Explanation will now be made with respect to the DDI of Windows NT4.0. The information regarding a StretchBlt function as a DDI function which can designate a magnification or a contraction of a bitmap is stored in StretchBlt 1019.

The area 1019 can store the information regarding this band such as the number of calling times callcnt 10191 of the StretchBlt function, the number of 1BPP images 1BPPCnt 10192, and a total data size 1BPPTotalSize 10193 of the 1BPP image.

Each of the other DDI functions, namely, CopyBits (1017), BitBlt (1018), ..., and Polygon (1020) also has a data structure such as to hold the information that is handed to each function I/F.

3) Process for reading device information, output environment information, layout information, and precheck results before despooling

Device information:

When the processing mode is determined from the collected information upon spooling, if the processing speeds of the graphics data, the processing speeds of the image data, or the logical operating abilities of the printers differ, there is a case where the prediction results differ. Those values are obtained every printer and stored in a file. The file is held as an installation file into the system.

002290"80050950

Output environment information:

It denotes an ability (CPU speed, disk speed, disk vacant capacity) of the host machine by which the printer driver operates and a transmission speed between the printer and the host.

Layout information:

The transmission data size in the case where the data is processed in the image mode largely changes in dependence on at which size the pageSize 1003 is actually outputted.

In case of arranging a plurality of pages to one page of the N-up designation or the like, there is a case where the pages which can be processed at a high speed in the PDL mode are collected and a load on the printer increases.

The page upon spooling is defined as a logical page and the page which is actually subjected to the drawing process upon outputting is defined as a physical page. Layout information shows at which positions in the physical page the logical pages are arranged.

Precheck result:

It shows the PCF in which the result checked by the spooler has been stored.

The PCFs of all of the logical pages existing in the physical page are read and used as targets of the arithmetic operation.

The following discriminating processes of <1> to <3> are made on a logical page unit basis and the discrimination results are held in a management table.

The presence or absence of a ColorRectL area (area where the drawing process of a chromatic color object was performed) of each band of the PCF is discriminated. If at least one of them exists, the relevant page is processed in the color mode.

The presence or absence of a ColorRectL area (area where the drawing process of a chromatic color object was performed) of each band of the PCF is discriminated. The band in which such an area exists is processed in the color mode.

The presence or absence of an ROPrectL area (area where the logical operating process by which an improper printing occurs in the YMCK color space was

In case of switching the processing mode on a band
5 unit basis:

```

10    The band where such an area exists is processed in the
    RGB24BPP image mode.

```

There is a relation as shown in Fig. 12 between the processing speeds in the image mode and the PDL mode.

An image mode processing 1200 is mainly divided into a processing time of the printer driver and a process of the printer.

20 Although the process of the printer driver relates
to a drawing time 1201 using the band memory, since the
drawing process including a color converting process
and a binarizing process is executed, it can be
regarded to be a process heavier than the process of
25 the driver in the PDL mode. The prediction value of
the processing time is obtained by multiplying the
drawing processing information of each drawing object

The processing time of the printer includes a data transmission time 1202, an intermediate data generation time 1203 in the printer, and a shipping time 1204. A draw area is first obtained to obtain the data transmission time 1202.

Since the intermediate data generation time 1203 in the printer has already been converted into the data format depending on the device, only the storing process of the intermediate data is performed, the processing time is proportional to the draw area, and a proportional coefficient is obtained from an apparatus kind dependency value.

The shipping time 1204 depends on an engine throughput speed.

The processing time in the image mode is obtained by obtaining the above total value.

5 "Prediction of PDL mode processing speed"

A PDL mode processing 1205 is also divided into a processing time of the printer driver and the process of the printer in a manner similar to the case of the image mode.

10 First, since the process of the printer driver is fundamentally only a command generation processing 1206 for converting the draw command handed from the system into the PDL command as it is, its processing speed is higher than that of the process of the driver of the
15 image mode system. Therefore, it is hardly influenced by the CPU speed of the host machine or the vacant disk capacity.

The PDL mode processing speed is predicted on the basis of a command generation prediction coefficient of
20 each object.

A data transmission time 1207 included in the processing time of the printer is influenced by a PDL command size and the speed of a transmission path. Since the size of the PDL command differs in dependence
25 on an output mode (color, monochromatic, etc.), the kind of apparatus, or a version of a language, the PDL command size of each object is calculated by using the

00605008.062700
002290"80050960

apparatus kind information collected by the despooler.
Also in case of reducing the size by the layout
process, since there is the data size which changes,
the PDL command size is calculated also in
5 consideration of the layout information.

A time that is required for working the received
data is set to a shipping preparation time 1208 so as
to be in time with the engine throughput of the
printer. If the intermediate data can be sufficiently
10 stored in the memory capacity of the printer, it is
possible to perform what is called a banding process
such that the drawing process and the shipping process
are alternately performed by using two band memories.
In this case, according to the processing speed of the
15 printer, the continuous pages can be printed by the
engine throughput. However, if the data exceeding an
intermediate data storage permission capacity of the
printer is transmitted or if a complicated arithmetic
operation is necessary and the banding process is not
20 in time, the printer abandons the banding process and
enters a special processing mode for assuring the
memory of one page. When the printer enters this mode,
the processing speed of the printer extremely
decreases. The time prediction in this instance
25 depends on the size of installed memory, the CPU speed
of the printer, or the ability of the hardware renderer
of the printer.

002290"80050960

5) Process for verifying whether the designated gradation output is possible by the selected reproducing means or not and selecting again the reproducing means by reducing the number of output gradations when it is determined that the designated gradation output is possible

Even in a printer which can perform a high gradation output, when the size of installed memory is small, a case where it is impossible to output by the designated number of gradations and the resolution also exists. Even in such a case, the page printer automatically degrades the resolution or the number of gradations in the printer in the PDL mode, thereby preventing an output impossible state from occurring.

However, if the device dependent bitmap (data which has already been subjected to a halftone process of the number of output gradations and the resolution) in the print data that is generated by the process in the image mode processing is subjected to the degrading process by the printer, the picture quality remarkably deteriorates. Therefore, the high gradation cannot be designated when the capacity of the installed memory of the printer is not guaranteed.

According to the embodiment, in order to provide a system for dynamically switching the PDL mode and the

The following methods are used to realize it.

5 (1) If the image mode is included in the selected processing system, the size (DataSize) at the time when the drawing commands of all of the logical pages included in the physical page have been converted into the intermediate data in the printer is predicted.

(3) When $DataSize > WorkSize$, the number of output gradations is decreased and the reproducing means is selected again.

A flow for a step of discriminating the logical pages in the physical page in the printer driver will now be described with reference to flowcharts of Figs. 13 and 14. A program regarding the flowcharts of Figs. 13 and 14 is stored in the memory of the host computer and executed by the CPU.

S1301: The optimum processing mode is determined every logical page in the physical page and step S1302

follows.

S1302: In the case where the device dependent bitmap exists in the output command, step S1303 follows. If such a bitmap does not exist, the processing routine is finished.

S1303: The size at the time when the print command in the logical page which is being calculated has been converted into the intermediate data in the printer is predicted and added to the total value (totalSize) of the intermediate data sizes of the pages calculated so far. Step S1304 follows.

S1304: When the data size obtained in step S1303 is larger than the size of intermediate data storing area calculated from the size of memory installed in the printer, step S1305 follows. When it is smaller, the processing routine is finished.

S1305: The number of gradations which is smaller than the designated number of gradations is set. The processing routine is returned to step S1301.

"Flow for a step of determining the processing system of each logical page"

S1401: One logical page information is obtained. Step S1402 follows.

S1402: In the case where the occurrence of the improper printing in the PDL mode is predicted, step S1412 follows. If there is no improper printing, step S1403 follows.

002290"80050960

S1411: When the logical page still exists, step S1401 follows. If there is no logical page, the processing routine is finished.

The despooling process is started at a timing when the processing systems and the number of processing gradations of all of the logical pages which are necessary to print one physical page.

After that, the PDF file is read every logical page and the process of the draw command is performed in the processing system decided in 5). In this instance, a layout converting process such as a process for changing, magnifying, or reducing the drawing position is realized by handing the draw command added with the layout converting process designated by a layout conversion unit (3034) to the processing system.

The printer enters a subclosing state when the size of print command is so large that the intermediate language of one page cannot be stored. In the

subclosing state, the intermediate languages accumulated so far are drawn into the memory space of one page, thereby releasing the memory in which the intermediate languages have been stored and enabling a print command to be newly read. In this instance, if the size of memory installed in the printer is small, the subclosing process cannot be performed by the designated number of gradations and the gradation is degraded. When the printer enters such a state, the processing speed of the printer remarkably decreases. Therefore, it is an effective processing mode switching to predict and avoid it.

The N-up printing process will now be described.

The N-up printing is a function which can designate the number of pages of a text formed by application software which can be printed on one paper by the printer driver. For example, the operation to print four pages onto one paper is called "4-up".

The N-up printing is realized by a method whereby a paper discharge command is not sent until the converting process of the data of N pages in the physical page is finished, thereby allowing the printer to process the print command of N pages as information of one page.

A flow for the N-up printing process after the processing system of the logical page unit was decided will be described with reference to a flowchart of Fig.

002290"80050960

17. A program regarding the flowchart is stored in the memory of the host computer 200 and executed by the CPU.

5 S1701: A translator module which was determined to perform the next logical page is loaded and step S1702 follows.

S1702: In case of the PDL mode, step S1710 follows. In case of the image mode, step S1703 follows.

10 S1703: The band memory which is used for the drawing process is obtained, the band height is calculated from the page width, and a band list is formed. Step S1704 follows.

S1704: The PDF (intermediate data) is linked to the band list formed in step S1703. Step S1705 follows.

15 S1705: A layout conversion module is initialized in accordance with the band area which will be processed from now on. Step S1706 follows.

20 S1706: The intermediate languages (PDF) linked to the band list for the current band are sequentially handed to the layout conversion module and a coordinate converting process is performed. Step S1207 follows.

25 S1707: The coordinate converted draw command is handed to the translator (image mode renderer) and the drawing process is executed on the prepared band memory space. Step S1708 follows.

S1708: If the data is still linked to the band list, step S1706 follows. If no data is linked thereto, step

002290-80050960

S1709 follows.

S1709: Device bitmap data (image data of 1, 2, or 4 bits per color of YMCK) is formed from the result drawn on the band and the print command is generated in consideration of the layout information obtained from the logical page position. Step S1710 follows.

S1710: If the processes for all bands were finished, step S1715 follows. If they are not finished yet, step S1705 follows.

S1711: The layout conversion module is initialized in accordance with the logical page area. Step S1712 follows.

S1712: The draw commands in the PDF are sequentially handed to the layout conversion module and the coordinate converting process is executed. Step S1713 follows.

S1713: The draw command subjected to the coordinate conversion is handed to the PDL translator and the print command is formed. Step S1714 follows.

S1714: If there is still a draw command in the PDF, step S1712 follows.

S1715: If there is still the logical page, step S1701 follows. If there is no logical page, the processing routine of the present job is finished.

A print command generating process in the N-up processing mode will now be described with reference to a schematic diagram of Fig. 18.

002250" 80050960

Reference numeral 1801 denotes a page of a heavy process to which the high resolution image used in the description also in Fig. 18 has been pasted. In case of processing the current page in the image mode, a memory area 1804 for the drawing process is obtained and used as a band memory 1805, thereby enabling the drawing process to be performed without having a memory space of the whole page.

In case of directly outputting at an equal magnification, the drawing memory of 4 Mbytes is used. To perform the processes of the page of the A4 size by the RGB24BPP image renderer, the memory is divided into 17 band areas having the height of bandH. (1803)

The spooled PDF has inherently been instructed so as to draw the image onto the page having a width W and a height H at the upper left position (0, 0) of the drawing origin page. To draw the image into the divided band memory areas, each band list for band is prepared and the PDF data regarding each band is linked again in the drawing designating order. The draw commands linked to the formed band list are handed to the translator (renderer) every band, thereby realizing the drawing process.

For example, as for the image data in the page 1801 in Fig. 18, the image defined by the upper left drawing position (X1, Y1) and the lower right drawing position (X2, Y2) exist in a range from the second to

002250" 80050960

5

10

$$Y2' = Y2 - \text{bandH} * \text{bandno.}$$

15

25

translator.

In case of processing the present page by the RGB24BPP image renderer, in order to perform the processes which are 1/4 of those of the A4 page by the RGB24BPP renderer, only four band memories are needed for the memory area of 4 Mbytes in a manner similar to the equal magnification.

Since the spooled PDF has inherently been instructed so as to draw an image onto the page having a width of W and a height of H, in order to perform the 4-up printing, such an area has to be coordinate converted into an area having a width w' and a height h' as shown at 1804. Although a band list for each band is formed in a manner similar to the case in the equal magnification printing mode, at this time, the coordinate values of the draw command in the PDF are converted into values in a coordinate space of the drawing destination. For example, the upper left drawing position (X1, Y1) and the lower right drawing position (X2, Y2) of the image data in the page 1801 are converted as follows, respectively.

$$(X1' = X1*(w'/W), \quad Y1' = Y1*(h'/H))$$

$$(X2' = X2*(w'/W), \quad Y2' = Y2*(h'/H))$$

The drawing process is realized by a method whereby the Y coordinate value of the converted drawing position of the data linked to the band list is further converted into the value of the coordinate system in

002230" 80050960

The output result developed in the band memory space of RGB24BPP around the formed pixel is color space converted into 8 bits per color of YMCK on a band unit basis and, thereafter, it is degraded to the number of output gradations (1, 2, or 4 bits per color) by the halftone process. The draw commands corresponding to the current logical pages can be obtained by adding the command of the image draw command converted into the drawing position for the 4-up printing to the generated data.

(Further detailed description on the printer side)

```
20      "Function for directly drawing device bitmap"
```

The data in the RGB color space is subjected to a color converting process in the printer and becomes device dependent color space data (YMCK) and held as intermediate data. At the time of drawing into the page memory, the intermediate data is subjected to the halftone process and becomes a device bitmap format whose gradations were degraded. According to the

invention, by adding the device bitmap data to the PDL command, the processing mode switching of the logical page unit is realized. The printer needs to have a processing system such that when the device bitmap data is received, it is held as intermediate data as it is and drawn in the page memory without performing the halftone process.

The mode selection and its flow will now be described with reference to Figs. 19 and 20.

Fig. 19 shows a graphic mode setting picture plane of the printer driver.

When an auto mode 1901 is designated, the mode is determined by the optimum mode determining process in Fig. 5 or 14, the data from the application is analyzed and converted into image data or PDL data, and transmitted to the printer.

When an image mode 1902 is designated, the image renderer 3036 is selected and the data from the application is converted into the image data and transmitted to the printer.

When a PDL mode 1903 is designated, the PDL 3035 is selected and the data from the application is converted into the PDL data and transmitted to the printer.

A graphic mode selecting process will now be described with reference to Fig. 20. A program regarding the flowchart of Fig. 20 is stored in the

002250" 80050960

memory of the host computer 200 and executed by the CPU.

Whether the auto mode has been designated or not is discriminated in step S2001. If YES, step S2002 follows. If NO, step S2003 follows.

In step S2002, the data from the application is analyzed by the process in Fig. 5 or 14, the optimum renderer is selected, and the data from the application is converted into the image data or PDL data by using the selected renderer and transmitted to the printer.

Whether the image mode has been designated or not is discriminated in step S2003. If YES, step S2004 follows. If NO, step S2005 follows.

In step S2004, the image renderer 3036 is selected and the data from the application is converted into image data by using the selected renderer and transmitted to the printer.

Whether the PDL mode has been designated or not is discriminated in step S2005. If YES, step S2006 follows. If NO, the processing routine is finished.

In step S2006, the PDL renderer 3035 is selected and the data from the application is converted into PDL data by using the selected renderer and transmitted to the printer.

(Third embodiment)

The third embodiment in the invention will now be described hereinbelow. In the embodiment, an

002290" 80050960

explanation of a construction similar to that of the first embodiment is omitted.

Although the switching method of the printing mode in the color mode of the color printer has been described in the first embodiment, the invention can be also applied to the monochromatic mode of a monochromatic printer or a color printer. A portion of the switching method in the monochromatic mode which is different from that in the color mode will be described hereinbelow. In the monochromatic mode, although it is unnecessary to check the color data among the following check items,

- <1> color data check
- <2> data size check
- <3> drawing speed check
- <4> logical operation value check

the other items are similarly checked and check results are similarly used as mode switching information.

In the monochromatic mode, in case of holding the data as monochromatic data in the printer, the size checked in the data size check is used.

The Device image mode to which the operating mode is shifted in the case where the speed becomes slow if the data is processed in the PDL mode due to the checks of <2> and <3> corresponds to the image mode of 1, 2, or 4 bits of Black.

The RGB24BPP image mode to which the operating

002290" 80050950

mode escapes in the case where an abnormality is detected by the logical operation value check of <4> is held as it is.

(Fourth embodiment)

5 The fourth embodiment of the invention will now be described hereinbelow. An explanation of a construction of the embodiment similar to that of the first embodiment is omitted here.

10 Although the first embodiment has been described with respect to the case where all of the PDL mode, Device image mode, and RGB24BPP image mode are provided, even in the case where one of them is not provided, by spooling and checking the data, the operating mode can be switched to the mode by which the
15 data can be most accurately outputted at the highest speed.

(Other embodiments)

20 The invention can be applied to a system comprising a plurality of apparatuses (for example, a host computer, an interface device, a reader, a printer, and the like) or can be also applied to an apparatus (for example, a copying apparatus, a facsimile apparatus, or the like) comprising one equipment.

25 Naturally, the objects of the invention can be also accomplished by a method whereby a storage medium on which software program codes called a printer driver

004290" 80050960

to realize the functions of the embodiments mentioned above have been recorded is supplied to a system or an apparatus and a computer (or a CPU or an MPU) of the system or apparatus reads out and executes the program codes stored on the storage medium.

In this case, the program codes themselves read out from the storage medium realize the functions of the embodiments mentioned above and the storage medium on which the program codes have been stored constructs the invention.

As a storage medium to supply the program codes, for example, a floppy disk, a hard disk, an optical disk, a magnetooptic disk, a CD-ROM, a CD-R, a magnetic tape, a non-volatile memory card, an ROM, or the like can be used.

Naturally, the invention also incorporates not only a case where the computer executes the read-out program codes, so that the functions of the embodiments mentioned above are realized, but also a case where the OS (Operating System) or the like which operates on the computer executes a part or all of the actual processes on the basis of instructions of the program codes and the functions of the embodiments mentioned above are realized by those processes.

Further, the invention obviously incorporates a case where the program codes read out from the storage medium are written into a memory provided for a

004290" 80050960

5

10

15

25

As described above, according to the invention,

the printing can be performed at a high speed by selecting the optimum converting means in accordance with the print data.

5 According to the invention, even when the N-up is designated, since the converting means is selected on a logical page unit basis, the printing can be performed at a high speed.

004290" 80050960